



TRANSLATION


Kenji Kobayashi, residing at 2-46-10 Goko-Nishi, Matsudo-shi, Chiba-ken, Japan, state:

that I know well both the Japanese and English languages;

that I translated, from Japanese into English, the specification, claims, abstract and drawings as filed in U.S. Patent Application No. 09/506,327, filed February 18, 2000; and

that the attached English translation is a true and accurate translation to the best of my knowledge and belief.

Dated: May 30, 2000


Kenji Kobayashi



TITLE OF THE INVENTION

IMAGE FORMING APPARATUS

BACKGROUND OF THE INVENTION

The present invention relates to an image forming apparatus and, more particularly, to an improvement in the developer replenishment mechanism of the image forming apparatus.

An image forming apparatus for forming an electrostatic latent image on an image carrier, developing the image with toner in a developing unit, and transferring the toner image onto a sheet, comprises a container (toner cartridge or toner bottle) for replenishing the developing unit with toner. This toner cartridge has a spiral on its inner surface. When the toner cartridge itself rotates, the contained toner is squeezed out from an outlet port along the spiral and supplied to the developing unit.

The outlet port of the toner cartridge is open in mounting a new toner cartridge on the apparatus main body or dismounting an empty toner cartridge from the apparatus main body. For this reason, toner escapes from the outlet port and scatters in the apparatus to contaminate the apparatus.

BRIEF SUMMARY OF THE INVENTION

It is an object of the present invention to provide a developer cartridge which prevents a developer from escaping from a outlet port and

scattering in an apparatus in mounting/dismounting
on/from the apparatus main body.

It is another object of the present invention to
provide an image forming apparatus having the developer
5 cartridge which prevents a developer from escaping from
the outlet port and scattering in the apparatus in
mounting/dismounting on/from the apparatus main body.

According to the present invention, there is
provided a developer cartridge which is rotatably
10 mounted in a developing unit of an image forming
apparatus, and supplies a developer to the developing
unit while rotating, comprising a cylindrical cartridge
main body having a developer outlet hole in an outer
surface near one end, and a ring-like cartridge-side
15 shutter which is fitted on the outer surface near one
end of the cylindrical cartridge main body to be
movable along a rotating shaft of the cylindrical
cartridge main body between a position where the
developer outlet hole is opened and a position where
20 the developer outlet hole is closed, wherein the
developing unit has a guide for inserting the developer
cartridge and a driving unit for rotating the developer
cartridge, the guide has a main body-side shutter with
a hole, and when the developer cartridge is mounted,
25 the cartridge-side shutter of the cylindrical cartridge
main body moves from the position where the developer
outlet hole is closed to the position where the

developer outlet hole is opened, the developer outlet
hole aligns itself with the hole of the main body-side
shutter, and every time the cylindrical cartridge main
body and the main body-side shutter integrally rotate
5 to align the developer outlet hole and the hole of the
main body-side shutter with a developer replenishment
port formed below the main body-side shutter, the
developer in the developer cartridge is supplied from
the developer replenishment port to the developing unit
10 via the developer outlet hole and the hole of the main
body-side shutter.

According to the present invention, there is
provided an image forming apparatus comprising a
developing unit for developing an electrostatic latent
15 image on an image carrier with a developer, and a
transfer unit for transferring the developed developer
image onto a transfer medium, wherein the developing
unit has a developer cartridge rotatably mounted
to supply the developer to the developing unit
20 while rotating, a guide for inserting the developer
cartridge, and a driving unit for rotating the
developer cartridge; the developer cartridge has
a cylindrical cartridge main body having a developer
outlet hole in an outer surface near one end, and
25 a ring-like cartridge-side shutter which is fitted
on the outer surface near one end of the cylindrical
cartridge main body to be movable along a rotating

shaft of the cylindrical cartridge main body between
a position where the developer outlet hole is opened
and a position where the developer outlet hole is
closed; the guide has a main body-side shutter with
5 a hole; and when the developer cartridge is mounted,
the cartridge-side shutter of the cylindrical cartridge
main body moves from the position where the developer
outlet hole is closed to the position where the
10 developer outlet hole is opened, the developer outlet
hole aligns itself with the hole of the main body-side
shutter, and every time the cylindrical cartridge main
body and the main body-side shutter integrally rotate
to align the developer outlet hole and the hole of the
15 main body-side shutter with a developer replenishment
port formed below the main body-side shutter, the
developer in the developer cartridge is supplied from
the developer replenishment port to the developing unit
via the developer outlet hole and the hole of the main
body-side shutter.

20 Additional objects and advantages of the invention
will be set forth in the description which follows, and
in part will be obvious from the description, or may be
learned by practice of the invention. The objects and
advantages of the invention may be realized and
25 obtained by means of the instrumentalities and
combinations particularly pointed out hereinafter.

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWING

The accompanying drawings, which are incorporated in and constitute a part of the specification, illustrate presently preferred embodiments of the invention, and together with the general description given above and the detailed description of the preferred embodiments given below, serve to explain the principles of the invention.

FIG. 1 is a sectional view showing the schematic structure of an image forming apparatus according to an embodiment of the present invention;

FIG. 2 is an exploded perspective view showing a toner replenishment unit of the image forming apparatus according to the embodiment of the present invention;

FIGS. 3A and 3B are views showing a state in which a toner cartridge is mounted in the toner replenishment unit;

FIGS. 4A and 4B are perspective views showing a state in which the toner cartridge of the image forming apparatus according to the embodiment of the present invention is positioned by an inlet guide to mesh with a driving unit;

FIGS. 5A, 5B, and 5C are schematic views showing exchange of the toner cartridge;

FIG. 6 is a perspective view showing a toner cartridge according to the embodiment of the present

invention;

FIG. 7 is a perspective view showing a state in which a cartridge-side shutter covers a toner outlet port in the toner cartridge according to the embodiment
5 of the present invention;

FIG. 8 is a perspective view showing a toner cartridge driving mechanism on the apparatus main body side according to the embodiment of the present invention;

FIG. 9 is a perspective view showing a toner cartridge according to another embodiment of the present invention;

FIG. 10 is a sectional view showing part of a toner cartridge according to still another embodiment
15 of the present invention; and

FIG. 11 is a perspective view showing part of the toner cartridge according to still another embodiment of the present invention.

DETAILED DESCRIPTION OF THE INVENTION

Preferred embodiments of the present invention
20 will be described below with reference to the several views of the accompanying drawing.

FIG. 1 is a sectional view showing a whole copying machine according to a preferred embodiment of the present invention. In FIG. 1, a copying machine 1
25 comprises at its lower portion a cassette sheet feeder 2 which stores many sheets. The copying machine 1

further comprises an LCF sheet feeder 3 for feeding many sheets of the same size, and a manual sheet feeder 4 capable of feeding various kinds of sheets.

5 The copying machine 1 comprises at its upper portion an image reading section 5 for reading a document, an automatic document feeder 6 for feeding a document to the image reading section 5, an image storage section 7 for storing image data read by the image reading section 5, and a laser optical device for
10 reading out the stored image data and writing the image on an image forming section 8.

The image forming section 8 is made up of a photosensitive drum 10, developing unit 11, cleaner 12, charger 13, discharge lamp 14, and transfer/separation
15 charger 15. The developing unit 11 is equipped with a toner cartridge 16 for replenishing the developing unit 11 with toner, and a driving unit 17 for driving the toner cartridge 16, as shown in FIG. 3A.

As shown in FIG. 3B, the outer surface of the toner cartridge 16 near its end has a projection 24 for
20 positioning the toner cartridge 16 in mounting it on the copying machine main body. The projection 24 stands at a predetermined position with respect to an outlet hole 21 formed in a cap (constricted
25 portion) 20.

FIG. 2 is an exploded perspective view showing the toner replenishment unit of the copying machine main

body. FIGS. 3A and 3B are views showing a state in which the toner cartridge is mounted in this toner replenishment unit.

5 In FIG. 2, an inlet guide 18 is attached to the copying machine main body, and has a guide hole of a size enough to receive the toner cartridge 16. As shown in FIG. 3B, a recess 25a is formed at a predetermined position of the guide hole. The recess 25a fits with the projection 24 formed on the toner
10 cartridge 16.

A mounting lever 25b is attached to the inlet guide 18. Upon mounting the toner cartridge 16, the mounting lever 25b presses the end of the toner cartridge 16 so as to prevent the toner cartridge 16
15 from popping out. A spring 26 for pressing the toner cartridge 16 into the copying machine main body is attached between the mounting lever 25b and the toner cartridge 16.

As shown in FIG. 3A, the copying machine main
20 body also comprises the driving unit 17 for rotating the toner cartridge 16. As shown in FIG. 2, the driving unit 17 is constituted by a motor 27, belt 28, pulley 29, driving gears 30 and 31, convey auger 32, driving gears 33 and 34, spring 35, driving plate 36,
25 holder guide 37, holder 38, and holder cover 39.

In this driving unit 17, the motor 27 rotates the pulley 29 via the belt 28 to rotate the driving gear 30

meshed with the pulley 29. The driving gear 30 meshes with the driving gears 31 and 33. The convey auger 32 is attached to the driving gear 31 and rotated by it.

5 The driving gear 33 meshes with the driving gear 34, to which the driving plate 36 is attached. The driving plate 36 has a driving hole for driving the toner cartridge 16. The driving gear 34 has an elliptical hole. The shaft of the driving plate 36 extends through the elliptical hole to allow the
10 driving gear 34 to slide axially with respect to the driving plate 36. The driving hole of the driving plate 36 is formed at a predetermined position with respect to the elliptical hole of the driving gear 34.

The holder guide 37 also has an elliptical hole.
15 The shaft of the driving plate 36 extends through this elliptical hole to connect the holder guide 37 to the driving gear 34. The holder guide 37 rotates integrally with the driving plate 36 by rotation of the driving gear 34.

20 The holder guide 37 has a toner replenishment hole 40, which is formed at a predetermined position with respect to the elliptical hole. A projection 41 stands at a predetermined position with respect to the elliptical hole of the driving shaft 34.

25 As shown in FIG. 3A, the toner cartridge 16 is mounted in the copying machine 1 after the mounting lever 25b on the front of the copying machine 1 is

released. At this time, the projection 24 of the toner cartridge 16 meshes with the recess 25a at the guide hole of the inlet guide 18.

The recess 25a is formed at, e.g., an upper portion of the guide hole of the inlet guide 18, and the projection 24 of the toner cartridge 16 corresponds in position with the recess 25a. The cap 20 of the toner cartridge 16 has the outlet hole 21 and a projection 22 at predetermined positions.

The toner cartridge 16 is positioned by the inlet guide 18 to mesh with the driving unit. That is, by positioning the toner cartridge 16 in this manner, the toner replenishment port 40 of the holder guide 37 of the driving unit 17 aligns itself with the outlet port 21 of the cap 20 to enable toner replenishment. At the same time, the projection 22 of the cap 20 fits in the driving hole of the driving plate 36 to enable rotating the toner cartridge 16 by the driving unit 17.

FIGS. 4A and 4B show a state in which the toner cartridge 16 is positioned by the inlet guide 18 to fit with the driving unit. FIG. 4A shows a state in which the inlet guide 18 and holder 38 are mounted, and FIG. 4B shows a state in which the inlet guide 18 and holder 38 are dismounted to expose the convey auger 32.

FIGS. 5A to 5C are schematic views showing exchange of the toner cartridge 16.

When toner in the toner cartridge 16 mounted in

the copying machine goes empty, an empty sensor arranged in the developing unit 11 displays an empty display on the control panel of the copying machine 1. Then, the user opens the front cover of the copying machine 1 to pull out the toner cartridge 16 axially (to the right on the page).

The toner cartridge 16 is pulled in a direction indicated by an arrow (to the right) from the state shown in FIG. 5A in which the toner cartridge 16 is mounted in the copying machine. FIG. 5B shows a state in which the toner cartridge 16 is pulled by 4 or 5 mm. In this state, the driving gear 34 is pressed to the right by the operation of the spring 35 to release the meshing between the driving gears 33 and 34. Hence, no rotation driving force is transferred from the driving gear 33 to the toner cartridge 16.

Further, the toner cartridge 16 is pulled to the right. FIG. 5C shows a state in which the toner cartridge 16 is pulled by 7 mm from the state of FIG. 5A. In this state, the toner cartridge 16 is disengaged from the driving plate 36.

After the toner cartridge 16 is dismounted, a new toner cartridge is mounted in the copying machine. The mounting procedures are reverse to the dismounting procedures described with reference to FIGS. 5A to 5C.

More specifically, the toner cartridge 16 is set at a predetermined position in the machine main body

(state shown in FIG. 5C), and pressed axially
(to the left on the page). Then, the projection 22 of
the cap 20 fits in the driving hole of the driving
plate 36 (state shown in FIG. 5B). In this state,
5 however, the driving gears 33 and 34 do not yet mesh
with each other.

The toner cartridge 16 is further axially pressed,
and the driving plate 36 and driving gear 34 move to
the left against the repulsion force of the spring 35.
10 The driving gear 34 meshes with the driving gear 33 to
allow rotation of the toner cartridge 16 by the driving
unit 17.

In this case, as described above, the toner
replenishment port 40 (not shown in FIGS. 5A to 5C)
15 of the holder guide 37 aligns itself with the outlet
port 21 (not shown in FIGS. 5A to 5C) of the cap 20 to
enable toner replenishment.

FIG. 6 is a perspective view showing a toner
cartridge according to the embodiment of the present
20 invention. In FIG. 6, a toner cartridge 100 has
a toner outlet port 101 on the side surface of
a constricted portion which is formed at one end of
the toner cartridge 100 and inserted into the inlet
guide 18. A spiral is formed on the inner surface of
25 the toner cartridge 100. Rotation of the toner
cartridge 100 squeezes toner in the toner cartridge 100
along the spiral, and when the toner outlet port 101

faces down, the toner is discharged from the toner outlet port 101.

5 The constricted portion at one end of the toner cartridge 100 is equipped with a cartridge-side shutter 102. As shown in FIG. 7, the cartridge-side shutter 102 covers the toner outlet port 101 before mounting the toner cartridge 100 in the machine main body or after dismounting it.

10 A toner scattering prevention seal 103 is attached to the toner outlet port 101 of the constricted portion at one end of the toner cartridge 100.

15 The cartridge-side shutter can have a through hole. That is, before the toner cartridge 100 is mounted in the machine main body, the cartridge-side shutter covers the toner outlet port 101. In mounting, the cartridge-side shutter moves axially to align the through hole with the toner outlet port 101.

20 FIG. 8 is a perspective view showing a toner cartridge driving mechanism on the machine main body side. In FIG. 8, a main body-side toner cartridge driving mechanism 200 has a coupling structure formed integrally with a main body-side shutter 201, which has a main body-side shutter opening 202. The constricted portion at one end of the toner cartridge 100 fits
25 with the main body-side shutter 201 so as to align the toner outlet port 101 with the main body-side shutter opening 202. Accordingly, the toner cartridge 100 is

mounted in the machine main body.

Before the toner cartridge 100 is mounted in the machine main body, the cartridge-side shutter 102 covers the toner outlet port 101, as shown in FIG. 7.

5 In mounting, the cartridge-side shutter 102 is pressed by the main body-side shutter 201 to slide and retract axially, thereby exposing the toner outlet port 101, as shown in FIG. 6.

10 The main body-side shutter 201 is rotated by the driving mechanism 200 to transfer the rotational force to the toner cartridge 100. The toner replenishment port (not shown) of the machine main body is formed below the main body-side shutter 201. Every time the main body-side shutter opening 202 and toner outlet
15 port 101 rotate and face down, toner in the toner cartridge 100 is discharged from the toner outlet port 101 and main body-side shutter opening 202. The toner is supplied to the machine main body through the toner replenishment port of the machine main body. In other
20 words, the toner is intermittently supplied by rotation of the toner cartridge 100.

The toner cartridge driving mechanism 200 having the coupling structure formed integrally with the main body-side shutter 201 can decrease the number of
25 components for rotating the toner cartridge 100, compared to a structure using a dedicated driving mechanism. This can reduce the product cost.

In dismantling the toner cartridge 100 from the machine main body, the cartridge-side shutter 102 is caught by the main body-side shutter 201 to slide forward and covers the toner outlet port 101. For this reason, toner does not scatter in dismantling the toner cartridge 100 from the machine main body.

To effectively replenish the developing unit with toner in the toner cartridge 100, a diameter a of the toner outlet port 101 of the toner cartridge 100, a diameter b of the main body-side shutter opening 202, and a diameter c of the toner replenishment port of the machine main body preferably satisfy a relation of $a \leq b \leq c$. When the hole is also formed in the cartridge-side shutter 102, as described above, a diameter d of this hole and the above holes preferably satisfy a relation of $a \leq d \leq b \leq c$.

If the main body-side shutter 201 is made of an elastic material such as rubber, it can function as a vibration insulator, and airtightness between the main body-side shutter 201 and the toner cartridge 100 can be enhanced. A conventional main body-side shutter is made of a flexible material such as plastic, and this material cannot satisfactorily enhance airtightness. By changing such material to rubber (natural rubber or silicone rubber), thermal deformation can be greatly suppressed.

FIG. 9 is a perspective view showing a toner

cartridge according to another embodiment of the present invention. In the toner cartridge shown in FIG. 9, a spiral 302 is formed on the inner surface of a constricted portion 301 of a toner cartridge 300 that fits with the machine main body. With this structure, the toner cartridge 300 is automatically dismounted from the machine main body by rotating the toner cartridge 300 counterclockwise.

In this case, claws 303 are attached near the other end of the toner cartridge 300. In counterclockwise rotation, the claws 303 are caught by the machine main body to stop rotation of the toner cartridge 300. However, the rotational force still acts to push the toner cartridge 300 in a direction indicated by an arrow by the operation of the spiral 302.

The toner cartridge 300 shown in FIG. 9 is axially supported by a roller 303. This roller 303 can be made of an elastic member such as rubber to obtain a high acoustic insulation effect.

FIGS. 10 and 11 are a sectional view and perspective view, respectively, showing the end of a toner cartridge according to still another embodiment of the present invention.

In a toner cartridge 400 shown in FIG. 10, a disconnection-prevention rib (projection) 404 is attached near the end of a constricted portion 401

of the toner cartridge 400 in order to prevent
a cartridge-side shutter 402 from slipping off
the constricted portion 401 of the toner cartridge 400.
When the cartridge-side shutter 102 slides on
5 the surface of the constricted portion 401 to close
a toner outlet port 403, the disconnection-prevention
rib 404 prevents the cartridge-side shutter 402 from
slipping off the constricted portion 401 of the toner
cartridge 400.

10 A position where the stopper rib 404 is formed is
a position where the cartridge-side shutter 402
completely covers the toner outlet port 403 when
the cartridge-side shutter 402 slides toward the
constricted portion 401 to a maximum degree.

15 The stopper rib 404 may be formed into a ring
shape on the entire constricted portion 401 of the
toner cartridge 400, but may be one or a plurality of
projections.

FIG. 11 shows still another embodiments of
20 a toner cartridge having a disconnection-prevention
structure for the cartridge-side shutter. In a toner
cartridge 500 shown in FIG. 11, the surface of
a constricted portion 501 and the inner surface of
a cartridge-side shutter 502 are threaded. Rotation of
25 the cartridge-side shutter 502 moves the cartridge-side
shutter 502 to open/close a toner outlet port 503.
Movement of the cartridge-side shutter 502 is stopped

at an unthreaded portion.

As has been described in detail above, the toner cartridge of the present invention has two, cartridge-side shutter and main body-side shutter.

5 Before mounting the toner cartridge in the developing unit, the toner outlet port of the toner cartridge is kept closed by the cartridge-side shutter. The toner replenishment port of the developing unit is kept closed by the main body-side shutter. Only in

10 mounting/dismounting the toner cartridge on/from the developing unit, the toner outlet port of the toner cartridge and the toner replenishment port of the developing unit are opened/closed. Accordingly, toner can be effectively prevented from scattering in the

15 developing unit in mounting/dismounting the toner cartridge on/from the developing unit.

Since the toner cartridge driving mechanism and main body-side shutter are integrated, the number of components can be decreased to reduce the cost.

20 Further, if particularly the main body-side shutter is made of an elastic material, it can function as a vibration isolator. At the same time, airtightness between the main body-side shutter and toner cartridge can be enhanced. Thermal deformation

25 can also be greatly suppressed.

Additional advantages and modifications will readily occur to those skilled in the art. Therefore,

the invention in its broader aspects is not limited to the specific details and representative embodiments shown and described herein. Accordingly, various modifications may be made without departing from the spirit or scope of the general inventive concept as defined by the appended claims and their equivalents.

5

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218
2219
2220
2221
2222
2223
2224

WHAT IS CLAIMED IS:

1. A developer cartridge which is rotatably mounted in a developing unit of an image forming apparatus, and supplies a developer to said developing unit while rotating, comprising a cylindrical cartridge main body having a developer outlet hole in an outer surface near one end, and a ring-like cartridge-side shutter which is fitted on the outer surface near said one end of said cylindrical cartridge main body to be movable along a rotating shaft of said cylindrical cartridge main body between a position where the developer outlet hole is opened and a position where the developer outlet hole is closed,
wherein said developing unit has a guide for inserting said developer cartridge and a driving unit for rotating said developer cartridge, said guide has a main body-side shutter with a hole, and when said developer cartridge is mounted, said cartridge-side shutter of said cylindrical cartridge main body moves from the position where the developer outlet hole is closed to the position where the developer outlet hole is opened, the developer outlet hole aligns itself with the hole of said main body-side shutter, and every time said cylindrical cartridge main body and said main body-side shutter integrally rotate to align the developer outlet hole and the hole of said main body-side shutter with a developer replenishment port

formed below said main body-side shutter, the developer
in said developer cartridge is supplied from the
developer replenishment port to said developing unit
via the developer outlet hole and the hole of said main
5 body-side shutter.

2. A developer cartridge according to claim 1,
wherein a diameter a of the developer outlet hole, a
diameter b of the hole of said main body-side shutter,
and a diameter c of the developer replenishment port
10 satisfy a relation of $a \leq b \leq c$.

3. A developer cartridge according to claim 1,
wherein said cartridge-side shutter has a hole, and
fits on said cylindrical cartridge main body so the
hole is movable between an opening position where the
15 hole aligns itself with the developer outlet hole and
a closing position.

4. A developer cartridge according to claim 3,
wherein a diameter a of the developer outlet hole, a
diameter d of the hole of said cartridge-side shutter,
20 a diameter b of the hole of said main body-side
shutter, and a diameter c of the developer replenish-
ment port satisfy a relation of $a \leq d \leq b \leq c$.

5. A developer cartridge according to claim 1,
wherein a spiral is formed on an inner surface of said
25 cylindrical cartridge main body.

6. A developer cartridge according to
claim 1, wherein said guide and said driving unit

are integrated.

7. A developer cartridge according to claim 1,
wherein a toner scattering prevention seal is attached
near the developer outlet hole of said cylindrical
5 cartridge main body.

8. A developer cartridge according to claim 1,
wherein said main body-side shutter is made of an
elastic material.

9. A developer cartridge according to claim 1,
10 wherein said cylindrical cartridge main body is
supported by a roller which is in contact with the
outer surface and made of an elastic material.

10. A developer cartridge according to claim 1,
wherein a projection for preventing said cartridge-side
15 shutter from slipping off is formed on the outer
surface near said one end of said cylindrical cartridge
main body.

11. A developer cartridge according to claim 1,
wherein an inner surface of said cartridge-side shutter
20 and a surface of said cylindrical cartridge main body
along which said cartridge-side shutter moves are
threaded to mesh with each other, and said cartridge-
side shutter is rotated to move on the surface of said
cylindrical cartridge main body and stops at an
25 unthreaded portion.

12. An image forming apparatus comprising
a developing unit for developing an electrostatic

latent image on an image bearing body with a developer,
and a transfer unit for transferring the developed
developer image onto a transfer medium,

5 wherein said developing unit has a developer
cartridge rotatably mounted to supply the developer
to said developing unit while rotating, a guide for
inserting said developer cartridge, and a driving unit
for rotating said developer cartridge;

10 said developer cartridge has a cylindrical
cartridge main body having a developer inlet hole
in an outer surface near one end, and a ring-like
cartridge-side shutter which is fitted on the outer
surface near said one end of said cylindrical cartridge
main body to be movable along a rotating shaft of said
15 cylindrical cartridge main body between a position
where the developer outlet hole is opened and a
position where the developer outlet hole is closed;

said guide has a main body-side shutter with
a hole; and

20 when said developer cartridge is mounted, said
cartridge-side shutter of said cylindrical cartridge
main body moves from the position where the developer
outlet hole is closed to the position where the
developer outlet hole is opened, the developer outlet
25 hole aligns itself with the hole of said main body-side
shutter, and every time said cylindrical cartridge main
body and said main body-side shutter integrally rotate

to align the developer outlet hole and the hole of said main body-side shutter with a developer replenishment port formed below said main body-side shutter, the developer in said developer cartridge is supplied from the developer replenishment port to said developing unit via the developer outlet hole and the hole of said main body-side shutter.

13. An image forming apparatus according to claim 12, wherein a diameter a of the developer outlet hole, a diameter b of the hole of said main body-side shutter, and a diameter c of the developer replenishment port satisfy a relation of $a \leq b \leq c$.

14. An image forming apparatus according to claim 12, wherein said cartridge-side shutter has a hole, and fits on said cylindrical cartridge main body so the hole is movable between an opening position where the hole aligns itself with the developer outlet hole and a closing position.

15. An image forming apparatus according to claim 14, wherein a diameter a of the developer outlet hole, a diameter d of the hole of said cartridge-side shutter, a diameter b of the hole of said main body-side shutter, and a diameter c of the developer replenishment port satisfy a relation of $a \leq d \leq b \leq c$.

16. An image forming apparatus according to claim 12, wherein a spiral is formed on an inner surface of said cylindrical cartridge main body.

17. An image forming apparatus according to claim 12, wherein said guide and said driving unit are integrated.

5 18. An image forming apparatus according to claim 12, wherein a toner scattering prevention seal is attached near the developer outlet hole of said cylindrical cartridge main body.

10 19. An image forming apparatus according to claim 12, wherein said main body-side shutter is made of an elastic material.

20. An image forming apparatus according to claim 12, wherein said cylindrical cartridge main body is supported by a roller which is in contact with the outer surface and made of an elastic material.

15 21. An image forming apparatus according to claim 12, wherein a projection for preventing said cartridge-side shutter from slipping off is formed on the outer surface near said one end of said cylindrical cartridge main body.

20 22. An image forming apparatus according to claim 12, wherein an inner surface of said cartridge-side shutter and a surface of said cylindrical cartridge main body along which said cartridge-side shutter moves are threaded to mesh with each other, and
25 said cartridge-side shutter is rotated to move on the surface of said cylindrical cartridge main body and stops at an unthreaded portion.

ABSTRACT OF THE DISCLOSURE

A developer cartridge which is rotatably mounted in the developing unit of an image forming apparatus, and supplies a developer to the developing unit while
5 rotating includes a cylindrical cartridge main body having a developer outlet hole in the outer surface near one end, and a ring-like cartridge-side shutter which is fitted on the outer surface near one end of the cylindrical cartridge main body to be movable along
10 the rotating shaft of the cylindrical cartridge main body between a position where the developer outlet hole is opened and a position where the developer outlet hole is closed. The developing unit has a guide for inserting the developer cartridge and a driving unit
15 for rotating the developer cartridge, and the guide has a main body-side shutter with a hole. When the developer cartridge is mounted, the cartridge-side shutter moves from the position where the developer outlet hole is closed to the position where the
20 developer outlet hole is opened, and the developer outlet hole aligns itself with the hole of the main body-side shutter. The cylindrical cartridge main body and the main body-side shutter integrally rotate to align the developer outlet hole and the hole of the
25 main body-side shutter with a developer replenishment port formed below the main body-side shutter. Every time this happens, the developer in the developer

cartridge is supplied from the developer replenishment port to the developing unit via the developer outlet hole and the hole of the main body-side shutter.




FIG. 1




FIG. 2




FIG. 3A




FIG. 3B




FIG. 4A




FIG. 4B

FIG. 5A




FIG. 5B





FIG. 5C






FIG. 6




FIG. 7




FIG. 8




FIG. 10




FIG. 11




FIG. 9

DECLARATION FOR PATENT APPLICATION

00S0052

As a below named inventor, I declare:

that I verily believe myself to be the original, first and sole (if only one individual inventor is listed below) or an original, first and joint inventor (if more than one individual inventor is listed below) of the invention in

IMAGE FORMING APPARATUS

COPY

the specification of which is attached hereto unless the following box is checked.

- ☐ was filed on _____ as United States Application
or PCT International Application No. _____, and
was amended on _____ (if applicable).

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information of which is material to patentability as defined in 37 CFR 1.56.


I hereby claim foreign priority benefits under 35 U.S.C. 119(a)-(d) or 365 (b) of any foreign application(s) for patent or inventor's certificate, or 35 U.S.C. 365(a) of any PCT International application which designated at least one country other than the United States, listed below and have also identified below any foreign application for patent or inventor's certificate, or PCT International application having a filing date before that of the application on which priority is claimed:

Country	Category	Application No.	Filing Date	Priority Claim
---------	----------	-----------------	-------------	----------------

And I hereby appoint Stephen A. Bent (Reg.No. 29,768), David A. Blumenthal (Reg.No. 26,257), William T. Ellis (Reg.No. 26,874), John J. Feldhaus (Reg.No. 28,822), Patricia D. Granados (Reg.No. 33,683), John P. Isacson (Reg.No. 33,715), Eugene M. Lee (Reg.No. 32,039), Richard Linn (Reg.No. 25,144), Peter G. Mack (Reg.No. 26,001), Brian J. McNamara (Reg.No. 32,789), Sybil Meloy (Reg.No. 22,749), George E. Quillin (Reg.No. 32,792), Collin G. Sandercok (Reg.No. 31,298), Bernhard D. Saxe (Reg.No. 28,665), Charles F. Schill (Reg.No. 27,590), Richard L. Schwaab (Reg.No. 25,479), Arthur Schwartz (Reg.No. 22,115) and Harold C. Wegner (Reg.No. 25,258), each of whose address is Suite 500, 3000 K Street, N.W. Washington, D.C. 20007-5109, or any one of them, my attorneys with full power of substitution and revocation, to prosecute this application and to transact all business in the Patent & Trademark Office connected therewith, and request that correspondence be directed to Foley & Lardner, Suite 500, 3000 K Street, N.W. Washington, D.C. 20007-5109.

I declare further that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

COPIES OF THIS DOCUMENT ARE AVAILABLE FROM THE PATENT & TRADEMARK OFFICE



DECLARATION FOR PATENT APPLICATION

I declare further that my citizenship, residence and post office address are as stated below next to my name:

Inventor: (Signature)

Date _____

Residence and post office address

Date: Feb. 16, 2000

1-17, Rokkakubashi Kazoku Apart,
40, Saitobuncho, Kanagawa-ku,

Citizen of: Japan

Yokohama-shi, Kanagawa-ken, Japan

Tokihiko Ise

Tokihiko Ise

Date:

Citizen of: Japan

Date:

Citizen of: Japan

Date :

Citizen of: Japan

Date:

Citizen of: Japan

Date:

Citizen of: Japan

Date:

Citizen of: Japan

Date:

Citizen of: Japan